

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Applicants: Jean-Pierre Bertin, et al.  
Filed: Herewith  
For: APPARATUS FOR RECEIVING AUDIOVISUAL  
PROGRAMS

5

PRELIMINARY AMENDMENT

Hon. Assistant Commissioner for Patents  
Washington, D.C. 20231

10

Sir:

Prior to examination and calculation of fees,  
please enter the following Preliminary Amendment and the  
accompanying remarks.

15

## IN THE CLAIMS

Please replace the claims with amended claims 1-9 as  
follows. A marked up copy of the amended claims is  
attached herewith.

20

1. (Amended) Apparatus for receiving audio-visual  
programs comprising a circuit for communication with  
means of connection to a bi-directional communication  
network, wherein the apparatus comprises :

25

- a first connector of a bus for communication with a  
master apparatus, the first connector comprising at  
least one conductor for the transmission of a supply  
voltage originating from the master apparatus,

30

- at least one second connector of a  
communication bus, each second connector allowing the  
connection of at least one peripheral,

35

- a splitter connected on the one hand to the  
first and second connectors and on the other hand to a  
controller managing the mode of operation of the  
connectors in relation to the apparatus,

- means of detection of the presence of the supply voltage in the first connector, the means of detection being linked to the first connector and generating a switching control signal on the appearance of the supply voltage to a switching circuit, so as to switch the apparatus from a first mode of operation to a second mode of operation.

2. (Amended) Apparatus according to Claim 1, wherein the first mode of operation is a so-called master mode of operation, in which the apparatus behaves as a master in relation to each peripheral, and in that the second mode of operation is a so-called peripheral mode of operation in which the apparatus behaves as a peripheral in relation to the master apparatus.

3. (Amended) Apparatus according to Claim 1, wherein the first connector is a B type USB connector and in that each second connector is an A type USB connector.

4. (Amended) Apparatus according to Claim 1, wherein the switching circuit comprises a quad switch, linked to the inputs/outputs of the controller and to the second connector, so as to allow the link between the second connector and the controller for a first given switching state.

5. (Amended) Apparatus according to Claim 1, wherein the switching circuit comprises a quad switch, linked to the inputs/outputs of the controller and to the inputs/outputs of a two-pathway splitter, itself linked to the first connector so as to allow in a second switching state the link between on the one hand the first connector and the controller and on the other hand the link from the first connector to the second connector.

6. (Amended) Apparatus according to Claim 4, wherein a link transmits the supply voltage detection signal so as to control the switching from one state to the other, to an input of the controller and to an input of the main microprocessor.

7. (Amended) Apparatus according to Claim 4, wherein,  
when the quad switch is switched into a first state, the  
apparatus operates in peripheral mode and when the quad  
switch is switched into a second state, the apparatus  
operates in master mode.

8. (Amended) Apparatus according to Claim 1, wherein  
the master apparatus is a personal computer and the  
apparatus comprises a digital decoder connected to the  
communication network so as to allow the computer to talk  
to the said network.

9. (Amended) Apparatus according to Claim 1, wherein  
the peripheral or peripherals are linked to the second  
connector of the apparatus by way of an additional  
splitter external to the decoder.

IN THE ABSTRACT

Please replace the abstract with the following:

5

--An apparatus for receiving audio-visual programs comprising a circuit for communication with means of connection to a bi-directional communication network, wherein the apparatus comprises: a first connector

10

comprising at least one conductor for the transmission of a supply voltage originating from the master apparatus; at least one second connector allowing the connection of at least one peripheral; a splitter connected on the one hand to the first and second connectors and on the other

15

hand to a controller managing the mode of operation of the connectors in relation to the apparatus; and means of detection of the presence of the supply voltage in the first connector, the means of detection being linked to the first connector and generating a switching control

20

signal on the appearance of the supply voltage to a switching circuit, so as to switch the apparatus from a first mode of operation to a second mode of operation.--

REMARKS


Claims 1-9 are pending. The claims, and the  
abstract have been amended to correct informalities. A  
5 marked up copy of the amended claims is attached  
herewith. No new matter is believed to be added.

No fee is believed due in regard to the present  
amendment. However, if a fee is due, please charge the  
fee to Deposit Account 07-0832.

10

Respectfully submitted,  
Jean-Pierre Bertin, et al.

15

  
By: Paul P. Kiel,  
Attorney for Applicants  
Reg. No. 40,677  
609-734-9650

20

Date: 8/31, 2001

25

THOMSON multimedia Licensing Inc.  
Patent Operations  
PO Box 5312  
Princeton, NJ 08543-5312

A marked up copy of amended claims:

[Claim] 1. (Amended) Apparatus for receiving audio-visual  
5 programs comprising a circuit for communication with  
means of connection to a bi-directional communication  
network, wherein the apparatus comprises:  
- a first connector of a bus for communication with a  
master apparatus, the first connector comprising at  
10 least one conductor for the transmission of a supply  
voltage [(VBUS)] originating from the master apparatus,  
- at least one second connector of a  
communication bus, each second connector allowing the  
connection of at least one peripheral,  
15 - a splitter connected on the one hand to the  
first and second connectors and on the other hand to a  
controller managing the mode of operation of the  
connectors in relation to the apparatus,  
- means of detection of the presence of the  
20 supply voltage [(VBUS)] in the first connector, the means  
of detection being linked to the first connector and  
generating a switching control signal on the appearance  
of the supply voltage [(VBUS)] to a switching circuit, so  
as to switch the apparatus from a first mode of operation  
25 to a second mode of operation.

[Claim] 2. (Amended) Apparatus according to Claim 1,  
wherein the first mode of operation is a so-called master  
mode of operation, in which the apparatus behaves as a  
30 master in relation to each peripheral, and in that the  
second mode of operation is a so-called peripheral mode  
of operation in which the apparatus behaves as a  
peripheral in relation to the master apparatus.

35 [Claim] 3. (Amended) Apparatus according to Claim 1,  
wherein the first connector is a B type USB connector and  
in that each second connector is an A type USB connector.

[Claim] 4. (Amended) Apparatus according to Claim 1, wherein the switching circuit comprises a quad switch, linked to the inputs/outputs of the controller and to the second connector, so as to allow the link between the  
5 second connector and the controller for a first given switching state.

[Claim] 5. (Amended) Apparatus according to Claim 1, wherein the switching circuit comprises a quad switch,  
10 linked to the inputs/outputs of the controller and to the inputs/outputs of a two-pathway splitter, itself linked to the first connector so as to allow in a second switching state the link between on the one hand the first connector and the controller and on the other hand  
15 the link from the first connector to the second connector.

[Claim] 6. (Amended) Apparatus according to Claim 4, wherein a link transmits the supply voltage detection  
20 signal so as to control the switching from one state to the other, to an input of the controller and to an input of the main microprocessor.

[Claim] 7. (Amended) Apparatus according to Claim 4, wherein, when the quad switch is switched into a first  
25 state, the apparatus operates in peripheral mode and when the quad switch is switched into a second state, the apparatus operates in master mode.

[Claim] 8. (Amended) Apparatus according to Claim 1,  
30 wherein the master apparatus is a personal computer and the apparatus comprises a digital decoder connected to the communication network so as to allow the computer to talk to the said network.

[Claim] 9. (Amended) Apparatus according to Claim 1, wherein the peripheral or peripherals are linked to the second connector of the apparatus by way of an additional  
35 splitter external to the decoder.